

| Serie | Schnittlänge | Banddicke * | Schnitt- winkel | Hubzahl | Antriebs- leistung | Tisch- breite | Arbeits- höhe | Abmessungen L x B x H |
|-----------|--------------|-------------|--------------------|----------------|-----------------------|------------------|------------------|--------------------------|
| | max. mm | max. mm | | max. 1/min. | | | | |
| TSQE 1330 | 1350 | 3,0 | 2,30° | 35 | 3,0 | 400 | 850 | 1700x1350x1200 |
| TSQE 2030 | 2050 | 3,0 | 2,12° | 35 | 3,0 | 400 | 850 | 2400x1350x1200 |
| TSQE 2525 | 2550 | 2,5 | 1,48° | 35 | 3,0 | 400 | 850 | 2900x1350x1200 |
| TSQE 3120 | 3100 | 2,0 | 1,30° | 35 | 3,0 | 400 | 850 | 3400x1350x1200 |
| TSQE 2040 | 2050 | 4,0 | 1,30° | 42 | 7,5 | 450 | 800 | 2550x2260x1330 |
| TSQE 2540 | 2550 | 4,0 | 1,30° | 42 | 7,5 | 450 | 800 | 3050x2260x1330 |
| TSQE 3140 | 3100 | 4,0 | 1,30° | 42 | 7,5 | 450 | 800 | 2650x2260x1330 |

*bei Zugfestigkeit 400 N/mm²